



Acusto - Sound Insulation (Anti-Sound Paint)

Acrylic copolymer emulsion based with mat appearance, sound insulation, high performance interior paint.

Areas of Use

An ideal paint to be used successfully on the previously painted or new and clear surfaces, interior and exterior walls covered with plaster concrete, brick, ytong, fiberboard, wood and other similar construction material.

Specifications

- Carefully selected colors and high quality give the surfaces a mat appearance.
- Gives no disturbing odor during the application.
- Dirt-free, easy to clean.
- Burn delay is available due to late burning.

Application

The surfaces subject to **Bianca Acusto - Sound Insulation Paint** application, must be clean and dry, free from all kinds of dirt, oil and dust, as well as old paint remainders. The surface must be smoothed with scrapper. The cracks must be repaired with acrylic based putty. The temperature of the surface and the surroundings must be min +5°C, Max +30°C. **Bianca Acusto - Sound Insulation Paint** should be thoroughly mixed before use. Apply at least 2 coats with roller or brush. After the surface preparation is completed, **Bianca Insulation Primer** is applied, after 6 hours **Bianca Acusto - Sound Insulation Paint** is applied.

Thinning (Volume)

Ready to use. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

Drying Period (20°C)

First Drying: 1/2 hours
Second Layer Application: 2 hours
Final drying: 24 hours

Coverage

For 1 mm thickness; 1 lt / 1 m² single coating.
For 2 mm thickness: 1 lt / 0,5 m² single coating.

Storage

Shelf life of the product is 1 year in its original can with the lid unopened.

Packing

15,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.