



Acrylic Based Exterior Primer

Acrylic copolymer emulsion based, surface filling, exterior white primer.

Areas of Use

For mineral based highly absorbent surfaces and also used before the first paint application.

Specifications

- Provides the adherence between the paint and the surface.
- Reduces the paint consumption.
- Prevents water and moisture penetration in great scale.
- Prevents the generation of moss and bacterium.
- Prevents ubnormal absorption of the paint by the surface.
- Increases the duration period of the paint.

Application

The surfaces subject to **Bianca Acrylic Based Exterior Primer (White Primer)** application must be clean and dry, free from all kinds of dirt, oil and dust. **Bianca Acrylic Based Exterior Primer (White Primer)** is applied as a first layer either with brush, roller or spraying. **Bianca Acrylic Based Exterior Paint** is used 6 hours after the application of **Bianca Acrylic Based Exterior Primer (White Primer)**. The temperature of the surface and the atmosphere, should be between +5°C, and. +30°C.

Thinning (Volume)

To be thinned with at most 10 % of water.

Drying Period (20°C)

Last layer Paint Application: 6 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 12 – 14 m².

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

2,50 / 15,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.