



Acrylic Based Exterior Grained Texture

Acrylic copolymer emulsion based, topcoat paint for exterior surfaces with mat appearance, excellent covering ability and grained texture.

Areas of Use

Mineral surfaces such as plaster, concrete and other cast surfaces, also used for decorative purposes to make designs on deformed plastering and defective surfaces.

Specifications

- **Bianca Acrylic Based Grained Texture** is developed by special filling materials.
- Shows a balanced drying nature.
- Complete fitness with applied surfaces.
- Excellent covering power.
- Resistant against all atmospheric conditions and pollution, also with special color pigments, against sunlight, friction and impacts.
- Non-fading and non-cracking.
- Releases moisture generated on the surfaces due to its respiration capability.
- Enables to work out various designs with changes in of roller and consumption material used.

Application

The surfaces subject to **Bianca Acrylic Based Grained Texture** application must be clean and dry, free from all kinds of dirt, oil and dust. 2 to 4 weeks drying period must be given to the newly plastered surfaces. **Bianca Acrylic Based Exterior Primer** must be applied to highly absorbent surfaces that are to be painted for the first time. It is a must to wait for at least 6 hours after the application of primer. **Bianca Acrylic Based Grained Texture** may be applied as a single layer to make designs on the surface by use of an appropriate roller. The temperature of the surface and the air temperature must be min +5°C max +30°C.

Thinning (Volume)

Directly applicable without thinning with water. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

Drying Period (20°C)

Final drying: 24 hours

Coverage

Depending on the application and the surface, for single layer, 1 kg will be enough to cover the 0,8 – 1,2 m².

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

25,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.