



Artístico - Creativo (Agleam)

Acrylic copolymer emulsion based, decorative, finishing layer interior surface paint with color and shine that changes according to the light, angle of view and surface color and can be wiped.

Areas of Use

All previously painted surfaces that are prepared, interior surfaces of concrete, plaster, black cast, betopan, glass textile and wall paper.

Specifications

Concentration: 1,05 ± 0,02 gr/ml

Application

The application surface must be smooth, solid, dry, clean and of the quality that would accommodate the paint. **Bianca Interior Wall Paste** must be applied on the application surface. After the paste applied surface is sanded, **Bianca Vals Water Based Satin Primer** must be applied to complete the surface preparation process. Following the primer application, wall paint must be applied in 2 layers on the surface. The most distinct gleaming effect can be achieved when the paint color on the surface is black. After the paint is dry, **Bianca Artístico Creativo** is applied on the surface by means of a roller or brush and when it is still wet the desired pattern is created by using decorative purpose application tools. The application must be made in a temperature range of +10°C and +30°C.

Due to its weak and chalking quality, sateen plaster should never be used on the surface. On surfaces with new plaster application, care must be taken to wait at least 28 days to apply paint on the surface.

Thinning (Volume)

The product is ready for use. It does not require dilution.

Drying Period (at 20°C, %65 HR)

Dryness to the Touch: 30 minutes

Complete Dryness: 24 hours

Waiting time between layers: 6 hours

Coverage

Depending on the surface smoothness and absorption capacity, a total of 145 - 190 ml/m² for 3 layers. A total of 5 - 6,5 m² of area can be painted with 1 lt of product in 3 layers. In a single layer 40 - 70 ml/m² consumption can be expected. To determine definite consumption amount; controlled sample test must be conducted.

Storage

The product can be stored for 2 years in its unopened package in a cool place, and protected against direct sunlight and frost.

Packing

0,75 / 2,50 / 7,50 / 15,00 lt

Hazard Classification

- Skin Irritation 1A; H317: May cause an allergic skin reaction

Precautionary Statements

-Precautions

- P261: Avoid breathing dust / fumes / gas / mist / vapours / spray.
- P272: Contaminated work clothing should not be allowed out of the workplace.
- P280: Wear protective gloves / protective clothing / eye protection / face protection.

-Intervention

- P302+P352: IF ON SKIN: Wash with plenty of water / ...
- P333+P313: If skin irritation or a rash occurs: Get medical advice / attention.
- P321: P321: Specific treatment (see ... on this label).
- P363: Wash contaminated clothing before reuse.

-Disposal

- P501: P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste." Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

Warning Word

Danger

Hazard Signs

