

TECHNICAL DATA SHEET
Document No: TDS.SU.006

Revision Date / No: 01.10.2018 / 00



# Artistico - Foglia (Foil)

Acrylic copolymer emulsion based, shiny, semi-opaque, metal looking decorative finishing layer of internal and external surface paint.

# Areas of Use

Application must be made on textured, acrylic and mineral based coatings and paintable wall paper after the preparation of the surface is completed.

## **Specifications**

Concentration:  $1,07 \pm 0,02$  (gr/ml)

## **Application**

The surface is prepared by means of textured application on newly or previously painted surfaces. Textured surface must be painted in a color that would be in harmony with the color of the finishing layer. In applications of *Bianca Artistico Foglia* in the color desired by means of a roller on painted surface, 4 hours standing period must be allowed between each layer and 2 layers must be applied. In applications on white surface, again 4 hour standing period must be allowed between each layer and 3 layers of the product must be applied. If the application surface is covered with wall paper, *Bianca Artistico Foglia* in a color desired will be applied 2 to 3 layers by means of a roller and by observing the drying times after the application of paint in a color recommended for the underlying surface.

## Thinning (Volume)

The product is ready for use. It does not require dilution.

#### Drying Period (at 20°C, %65 HR)

Dryness to the Touch: 45 minutes Complete Dryness: 24 hours

#### Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 9 - 12 m<sup>2</sup>. To determine definite consumption amount; controlled sample test must be conducted.

### Storage Hazard Statements

The product can be stored for 2 years in its unopened package, in a cool place, and protected against direct sunlight and frost.

#### **Packing**

0,75 / 2,50 / 7,50 / 15,00 lt

#### Hazard Classification

• Skin Irritation 1A; H317: May cause an allergic skin reaction

### **Precautionary Statements**

# - Precautions

- P261: Avoid breathing dust / fumes / gas / mist / vapours / spray.
- P272: Contaminated work clothing should not be allowed out of the workplace.
- P280: Wear protective gloves / protective clothing / eye protection / face protection.

#### - Intervention

- P302+P352: IF ON SKIN: Wash with plenty of water / ...
- P333+P313: If skin irritation or a rash occurs: Get medical advice / attention.
- P321: Specific treatment (see ... on this label).
- P363: Wash contaminated clothing before reuse.



TECHNICAL DATA SHEET

Document No: TDS.SU.006
Revision Date / No: 01.10.2018 / 00

### - Disposal

• P501: P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste." Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

# **Warning Word**

Danger

## **Hazard Signs**

