

TECHNICAL DATA SHEET

Document No: TDS.SU.007

Revision Date / No: 01.10.2018 / 00



# Artistico - Linea (Grainy Metallic Texture)

Water based grainy textured, glossy and decorative finishing interior surface paint. .

#### Areas of Use

Can be applied on all previously painted surfaces that are prepared, interior surfaces of concrete, plaster, black cast, betopan, glass textile and wall paper.

# **Specifications**

Concentration:  $1,25 \pm 0,02$  (gr/cm<sup>3</sup>)

## **Application**

The application surfaces must be smooth, durable, humidity-free and self-accommodating. The coatings on previously painted, glass textile, or wall paper covered surfaces must be removed, if possible, and a smooth and even surface must be obtained by applying *Bianca Interior Wall Paste*. After the paste applied surface is sanded, *Bianca Vals Water Based Satin Primer* must be applied to complete the surface preparation process. Due to its weak and chalking quality, sateen plaster should never be used in preparing the surface. *Bianca Artistico Linea* is applied on the surface without dilution and by means of a decorative brush creating horizontal, vertical or diagonal patterns as desired. When the product is about to dry, the liquid on grainy texture of the product is removed by applying slight pressure with a clean and thick brush. This will ensure that the grainy texture achieves an opaque appearance while the background remains glossy.

After the application is completed the tools must be cleaned immediately with water.

Prior to use the paint must be thoroughly mixed until it becomes homogeneous.

Do not apply the product at temperatures lower than +5°C.

Prior to an application on glossy and glassy surfaces, the surface must be sanded to establish a solid base to achieve better adhesion. .

## Thinning (Volume)

The product is ready for use. It does not require dilution.

# Drying Period (at 20°C, %65 HR)

Dryness to the Touch: 30 minutes Complete Dryness: 24 hours

Waiting time between layers: 4 - 6 hours.

#### Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 5 - 7 m<sup>2</sup>. To determine definite consumption amount; controlled sample test must be conducted.

## Storage

The product can be stored for 2 years in its unopened package, in a cool place, and protected against direct sunlight and frost.

# **Packing**

0,75 / 2,50 / 7,50 lt

#### Hazard Classification

Skin Irritation 1A; H317: May cause an allergic skin reaction

### **Precautionary Statements**

- Precautions
- P261: Avoid breathing dust / fumes / gas / mist / vapours / spray.



TECHNICAL DATA SHEET
Document No: TDS.SU.007

Revision Date / No: 01.10.2018 / 00

- P272: Contaminated work clothing should not be allowed out of the workplace.
- P280: Wear protective gloves / protective clothing / eye protection / face protection.
- Intervention
- P302+P352: IF ON SKIN: Wash with plenty of water / ...
- P333+P313: If skin irritation or a rash occurs: Get medical advice / attention.
- P321: Specific treatment (see ... on this label).
- P363: Wash contaminated clothing before reuse.
- Disposal
- P501: P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste." Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

## Warning Word

Danger

## **Hazard Signs**

