



Artístico - Madreperla (Pearl Textured Nacre)

Final-coat interior wall-painting on acrylic-polymer-emulsion basis, washable, decorative with pearlescent texture.

Areas of Use

Applicable on all ground prepared surfaces like old painting, concrete, plaster, black cement plaster, precast concrete panels, glass textiles and wall paper.

Specifications

Colour: Selectable from the Bianca Special Effected and Textured Items Catalogue.
Brightness 60°: 44± 5 gloss
Density: 1,05 ± 0,02 g/ml

Application

All surfaces to be applied should be flattened, fixed, dry and clean and should be able to carry the painting. The surface must be filled with **Bianca Interior Wall Paste**. After sanding the filled surfaces, apply Bianca **Vals Water Based Satin Primer** and finish the surface preparation works. If colour differences are wanted in the background, **Bianca Artístico Madreperla** (pearl textured nacre) can be applied over the first and second coat wall painting with a satin roll as single coat and design is given by a second person before it is dried out. If no colour difference is wanted, apply just like normal wall painting with a satin roll as single coat on the wall. After first coat painting is dry, second coat is applied with a fluffy roll onto the surface and while the painting is still wet designs can be given with tools like effect rolls, sea sponges and buckskin. Application should be done at temperatures between +10°C and +30°C. In cases where other colours than the ones shown in the Bianca Special Effected and Textured Items Catalogue are wanted, colour tone differences may occur due to application methods. In this case it is advised to perform a draft painting. For surface preparation it is absolutely advised to use satin plaster due to its weak and dusty condition. On freshly plastered surfaces, in order to start with the wall painting please be sure to have waited at least 28 days.

Thinning (Volume)

Ready to use. Do not dilute.

Drying Period (at 20°C, %65 HR)

Surface dry out after: 30 minutes
Fully dry in: 24 hours
Waiting time between coats: 6 hours

Coverage

According to surface smoothness and absorbency, at 3 coats in total approximately 145 - 190 ml/m². With 1 lt and 3 coats in total, a space of 5 - 6,5 m² can be painted. Consumption at single coat is approximately 40 - 70 ml/m². For exact consumption please perform a controlled sample painting.

Storage

Storage up to 2 years is possible, when not opened, stored in a cool place without direct sunlight and no frost.

Packing

0,75 / 2,50 / 7,50 / 15,00 lt

Hazard Classification

- Skin Irritation 1A; H317: May cause an allergic skin reaction

Precautionary Statements

- Precautions

- P261: Avoid breathing dust / fumes / gas / mist / vapours / spray.
- P272: Contaminated work clothing should not be allowed out of the workplace.
- P280: Wear protective gloves / protective clothing / eye protection / face protection.

- Intervention

- P302+P352: IF ON SKIN: Wash with plenty of water / ...
- P333+P313: If skin irritation or a rash occurs: Get medical advice / attention.
- P321: Specific treatment (see ... on this label).
- P363: Wash contaminated clothing before reuse.

- Disposal

- P501: P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste." Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

Warning Word

Danger

Hazard Signs

