

TECHNICAL DATA SHEET
Document No: TDS.SU.009

Revision Date / No: 01.10.2018 / 00



Artistico - Marmorino (Marbel Texture)

Water based semi-glossy decorative and aesthetic interior surface finishing paint that gives a marble effect.

Areas of Use

All previously painted surfaces that are prepared, interior surfaces of concrete, plaster, black cast, betopan, glass textile and wall paper.

Specifications

Concentration: 1,65±0,02 gr/ml

Application

The application surface must be smooth, solid, dry, clean and of the quality that would accommodate the paint. The coatings on previously painted, glass textile, or wall paper covered surfaces must be removed, if possible, and a smooth and even surface must be obtained by applying *Bianca Interior Wall Paste*. After the paste applied surface is sanded, *Bianca Vals Water Based Satin Primer* must be applied to complete the surface preparation process. Due to its weak and chalking quality, sateen plaster should never be used on the surface. On the surface that is prepared as indicated above, *Bianca Artistico Marmorino* must be applied by using a trowel in a single layer by spreading the product without dilution in the consistency of a paste. Before the surface is completely dry, a second layer of application is made with the help of a trowel. The surface is smoothed out by circular motion applied through the sides moving from outside towards inside. After the surface dries, the third layer must be applied with a spatula in a patch pattern. Immediately following the application, and before the product is dry, the polishing process must be started with the help of a trowel. Application must be made with care without applying too much pressure on the surface. If too much pressure is applied on the surface, it will appear as if the surface is scratched. After the polishing process is completed, the surface must be allowed to dry for 24 hours.

Thinning (Volume)

The product is ready for use. It does not require dilution.

Drying Period (at 20°C, %65 HR)

Dryness to the Touch: 30 minutes Complete Dryness: 24 hours

Waiting time between layers: 4 - 6 hours.

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 10 - 12 m². To determine definite consumption amount; controlled sample test must be conducted.

Storage

The product can be stored for 2 years in its unopened package, in a cool place, and protected against direct sunlight and frost.

Packing

3,50 / 23,00 kg



TECHNICAL DATA SHEET

Document No: TDS.SU.009
Revision Date / No: 01.10.2018 / 00

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.