



Artístico - Texturo

It is an acrylic emulsion based interior-exterior surface coating material of grainy, opaque structure that can be applied in a single layer by means of a roller which is also used to create a pattern.

Areas of Use

It is used on plaster, concrete, rough rendered and other mineral surfaces as well as to make patterns on deficient and deficiently plastered surfaces.

Specifications

- The product conforms extremely well to the surfaces it is applied to. It has superior adhesive strength.
- Various patterns can be created by means of a roller and based on the amount used.

Application

The application surface must be free of all types of dirt, oil and dust. Remains of old paints must be removed and the surface must be left clean and dry. Newly plastered surfaces must be allowed to stand for 2 to 4 weeks to ensure necessary dryness. For very absorbent surfaces that will be painted the first time, it will be necessary to use a primer. Before starting the application, at least 6 hours must be allowed after the application of the primer. After a roller commensurate with the pattern desired is selected, a single layer of **Bianca Artístico Texturo** is applied on the surface. During application the minimum and maximum ambient and surface temperatures must be +5°C and +30°C respectively.

Thinning (Volume)

The product is ready for use.

Drying Period (at 20°C, %65 HR)

Final Drying Time: 24 hours.

Coverage

Depending on the desired pattern, the consumption is 500 to 1200 g/m². 1 kg of product is required to polish an area of 1 - 2 m² in a single layer. To determine definite consumption amount; controlled sample test must be conducted.

Storage

The product can be stored for 2 years in its unopened package, in a cool place, and protected against frost.

Packing

25,00 kg

Hazard Classification

- Skin Irritation 1A; H317: May cause an allergic skin reaction.

Precautionary Statements

- Precautions

- P261: Avoid breathing dust / fumes / gas / mist / vapours / spray.
- P272: Contaminated work clothing should not be allowed out of the workplace.
- P280: Wear protective gloves / protective clothing / eye protection / face protection.

- Intervention

- P302+P352: IF ON SKIN: Wash with plenty of water / ...
- P333+P313: If skin irritation or a rash occurs: Get medical advice / attention.
- P321: Specific treatment (see ... on this label).
- P363: Wash contaminated clothing before reuse.

- Disposal

- P501: P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste." Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

Warning Word

Danger

Hazard Signs

