



Asphalt Paint - ASF 20

Bianca Asphalt Paint with two component product combines the flexibility and strength of asphalt with leading-edge coating technologies.

Areas of Use

For new and old asphalts.

Specifications

- No-fading, no cracking, no blistering and no spilling.
- Gives no disturbing odor during the application.
- Dirt-free, like the first day, keep the property for many years.
- Time and labor saving due to high spreading power on the surface.
- Bianca Asphalt Paint will increase durability of asphalt three times more durable.
- Due to the UV resistance coloring, it provides excellent protection against harmful UV sunlight.
- Resistant to all atmospheric conditions and pollution, sunlight, friction and impacts.
- **Bianca Asphalt Paint** is provides waterproofing.

Application

The surfaces subject to paint application must be clean and dry, free from all kinds of dirt, oil and dust, as well as old paint remainders. The temperature of the surface and the surroundings must be min. +5°C, Max. +30°C. Slowly add Component A into the package of component B and mixed thoroughly for 3 - 5 minutes. High performance product are applied using a sprayer or applied by brush.

Thinning (Volume)

Ready to use.

Mixing Ratio (Weight)

A Component: 16,5 kg
B Component: 6,5 kg

Drying Period (20°C)

First Drying: 15 min.
Second Layer Application: 2 hours
Final drying: 24 hours

Coverage

1 - 1.4 m² area can be painted with 1 kg.

Storage

Shelf life of the product is 2 year in its original can with the lid unopened.

Packing

Set Total: 23,00 kg (16,50+6,50) kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.