



Binder - Insulating Material and Primer

Water based, acrylic copolymer silicone paint primer and isolation material.

Areas of Use

Applicable on all kinds of plaster, concrete, satin casting, special kind of eternite plate surface.

Specifications

- Water preservation capability due to silicone structure.
- Prevents water leakage in the lavatories and bathrooms.
- Reduces the absorption capacity of the surfaces on finished walls, plaster, satin casting or pasted surfaces and reduces the paint consumption.
- Enables the adherence of the paint on the surface by reinforcing the existing old paints..

Application

The surfaces subject to **Bianca Binder** application must be clean and dry, free from all kinds of dirt, oil and dust. It can be applied either with brush or roller at min. +5°C, max +30°C.

Thinning (Volume)

For first layer dilute 1 part **Bianca Binder** with 4 parts water, second and third layers dilute 1 part **Bianca Binder** with 2 parts water.

Drying Period (20°C)

Final drying: 1 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 25 - 40 m².

Storage

Shelf life of the product is 2 years when stored in a cool place protected from freezing.

Packing

1,00 / 4,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.