



Boypen - PVC Paint

Acrylic copolymer based emulsion paint for PVC. Extra white, glossy and highly covering.

Areas of Use

Can be applied and all kinds of PVC surfaces.

Specifications

- It does not include solvents and is diluted by using water and does not smell.
- It is not harmful for human health and environment.
- Resistant to UV and heat. It does not turn yellow or crack with the passage of time.
- Due to its water base it dries fast. In 3 -5 hours the second layer can be applied.
- Its glossy appearance is enduring.
- Waterproof, it can be wiped, cleaned and rubbed.
- Has a superior coverage capacity.
- Can be used inside and outside on PVC windowsills..

Application

The surfaces on which **Bianca Boypen** is to be applied must be cleaned. The paint is applied in temperatures above 50C. In case if needed, the surface must be cleaned and smoothed by using fine emery/sand paper. **Bianca Boypen** is applied in two layers. Between the application of layers a 5 hour period must elapse. **Bianca Boypen** can be applied by using a brush, or a roll or by spraying.

Thinning (Volume)

Use water for diluting the paint and dilute maximum 10% for the first and the second layer of the paint. It can also be applied without dilution. Before using the paint mix it well and do not mix it with paint of another brand.

Drying Period (20°C)

Initial Drying: 1 hour
Second Layer Application: 5 hours
Final Drying: 24 hours
Endurance tests can be held after 4 days.

Coverage

With 1 liter, based on the application method and type of the surface, 10 - 14 m² area can be covered in single layer.

Storage

Shelf life of the product is 2 year in its original can with the lid unopened.

Packing

0,75 / 2,50 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.