



Gross Concrete Primer

Acrylic polymer emulsion based, white pigmented gross concrete primer with surface filling quality.

Areas of Use

Can be used as a primer to increase adherence and the work period on gross concrete surfaces with high water absorption quality, as well as on walls and ceilings, and under cement and specially gypsum plaster.

Specifications

- Establishes a connective "bridge" between the plaster and surface.
- Prevents seeping of water and humidity to a great extend.
- Improves the useful life of the plaster.

Application

The surface on which **Bianca Gross Concrete Primer** is to be applied, must be cleaned to eliminate all kinds of dirt, grease and dust and furthermore it must be dry. **Bianca Gross Concrete Primer** is applied in one layer by using a roll. After 6 hours following the application of **Bianca Gross Concrete Primer**, the plaster can be applied. During the application, temperature of the environment and surface as it must at least be between +5°C and +30°C. It is required that the plaster is applied at most within 7 days after applying **Bianca Gross Concrete Primer**.

Thinning (Volume)

Thinning with water up to 20% is possible.

Drying Period (20°C)

Plaster Application: 6 hours

Coverage

Depending on the application and the surface, for single layer, 1 kg will be enough to cover the 3 - 5 m².

Storage

Its shelf life is 1 year at room temperature in its original packaging.

Packing

3,00 / 12,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.