



Corte - Tennis Court Coating

Acrylic copolymer emulsion based tennis court coating with mat appearance.

Areas of Use

Used on all types of concrete except tennis courts, open stock reservoirs, entrance, corridor and non-absorbent concrete.

Specifications

- Excellent covering ability.
- No-fading, no cracking, no blistering and no spillinng.
- Resistant to all atmospheric conditions and pollution, sunlight, friction and impacts.
- Time and labor saving due to high spreading power on the surface.
- Gives mat appearance to the surfaces its carefully selected colors and high quality.
- Gives no disturbing odor during application.

Application

The surfaces subject to **Bianca Tennis Court Coating** application must be clean and dry, free from all kinds of dirt, oil and dust, as well as old paint remainders. The surface must be smoothed with scrapper. The cracks must be repaired with acrylic based putty. The temperature of the surface and the surroundings must be min.+5°C, Max. +30°C. In order to prevent streaky movements on the wide surface, the material should always be thinned with same amount of water, thoroughly mixed, and be applied without break. There should be no extreme wind or air circulation in the application area. The first layer of paint is applied to the surface as a primer and then **Bianca Tennis Court Coating** application is applied after 6 hours.

Thinning (Volume)

To be thinned with at most 10 % of water.

Drying Period (20°C)

First Drying:1/2hours
Second Layer Application:2hours
Final drying:24hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 6 - 8 m².

Storage

Shelf life of the product is 1 year in its original can with the lid unopened.

Packing

15,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.