



Interior Filling Primer

Acrylic copolymer emulsion based, surface filling, white interior primer.

Areas of Use

Mineral based highly absorbent surfaces and also used before the first paint application.

Specifications

- Forms a link between the paint and the surface.
- Reduced the paint consumption.
- Avoids water and moisture penetration in great scale.
- Avoids differential absorption of the paint by the surface.
- Increases the duration period of the paint.

Application

The surfaces subject to **Bianca Interior Filling Primer** application must be clean and dry, free from all kinds of dirt, oil and dust. **Bianca Interior Filling Primer** is applied as a first layer either with brush, roller or spraying. Topcoat paint is used 6 hours after the application of **Bianca Interior Raw Plaster Primer**. Attention should be given to the temperature of the surface and the atmosphere, preferably to be kept at min. +5°C, max. +30°C.

Thinning (Volume)

To be thinned up to 30% with water.

Drying Period (20°C)

Last layer Paint Application: 6 hours

Coverage

Depending on the application and the surface, for single layer, 1 kg will be enough to cover the 4 - 8 m².

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

3,50 / 20,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.