



Elastic Exterior Wall Coating

Acrylic copolymer emulsion based elastic exterior surface coating substance.

Areas of Use

Applicable to plaster, concrete, brick and wooden surfaces. Successfully used in the areas where the sea water and moisture is highly effective.

Specifications

- Non-oxidizing, resistant to salt, moisture and weak chemical solvents.

- Avoids the generation of bacterium.
- Resistant to ultra-violet rays.
- Can be washed surface detergent or soaped water.
- Semi-gloss appearance.
- Does not loose its elastic nature within time.
- Hides the very fine cracks due to its elastic nature.
- Enables to work out various designs on the applicable surface by change of roller.
- Walls continuously remain dry due to its water-repellent nature. By this way, the loss of heat, surface pollution, formation of moss and mold is minimized.

Application

Applicable surfaces must be clean and dry, free from old painting remains, all kinds of dirt, oil and dust. **Bianca Acrylic Based Exterior Primer** must be applied to the highly absorbent surfaces that are to be painted for the first time. At least 6 hours should pass after the application of the primer. Then **Bianca Elastic Exterior Wall Coating** paint should be applied. The surface and air temperature should be min.+5°C and max. +30°C.

Thinning (Volume)

Directly applicable without thinning with water. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

Drying Period (20°C)

Final Drying: 24 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 1 - 1,2 m².

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

15,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.