



Espina Soft Mat

Water and emulsion based, matte, decorative interior surface top coat paint containing silicone.

Areas of Use

Used safely as a top coat paint on new mineral based interior walls and ceilings, old painted and faded surfaces, surfaces whose subsurface preparation operations such as satin gypsum and paste have been completed, glass textile and wall papers as well as interior surfaces of balconies.

Specifications

- It is enhanced with silicone technology.
- It performs high durability and coveringability.
- It has a special soft matte texture.
- Espina is an optimum paint which has wipe clean capability.
- It integrates with the applied surface.
- It shows high capability of breathing.
- Causes no cracking, blistering or spalling
- Makes labor saving during application with its spreadingability.
- Since it is waterbased, it does not emit any disturbing odor; environment friendly.

Application

The surfaces subject to **Bianca Espina** paint application must be clean and dry, free from all kinds of dirt, oil and dust. The old paints must be scraped and removed. The cracks on the wall must be filled with satin plaster or paste. During application, care should be taken that the surface and ambient temperature is between min. +5°C and max. +30°C. After the surface preparation is completed, to line with **Bianca Vals Primer** will increase adherence and provide significant economy at paint consumption. It is applied single coat with brush or roller as top enetrate the surface exactly and equally. To avoid fluctuations on large surfaces, the paint should always be diluted with the same amount of water, thoroughly mixed and applied without interruption to the surface. There should not be excessive wind and air flow in the application environment. After 6 hours **Bianca Espina** application is done.

Thinning (Volume)

To be thinned with %15-20 of water for both 2 layers too. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

Drying Period (20°C)

First Drying Time: 30-60 minutes.
Second Layer Application: 4-6 hours.
Final Drying Time: 24 hours
(drying time could prolong at higher relative humidity and low temperatures.)

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 10 - 14 m².

Storage

An area of 13-18 m² can be painted at one coat with 1 liter of Espina paint.

Packing

0,75 / 2,50 / 15,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.