



Forza Plastik

Acrylic copolymer emulsion based decorative economical topcoat wall paint for interior and exterior surfaces, with mat appearance, white color and covering capability.

Areas of Use

An ideal plastic paint to be used successfully on the previously painted and non-faded surfaces, interior and exterior walls covered with plaster concrete, brick, fiberboard, wood and other similar construction materials.

Specifications

- Water based, with high respiration capability.
- Complete fitness with the applied surfaces ; no cracking, no blistering and no spilling.
- Non-faded due to its qualified pigment structure, white color and covering capability.
- Gives mat and smooth appearance to the surfaces with its carefully selected colors and high quality.
- Gives no disturbing odor during the application.

Application

The surfaces subject to **Bianca Forza Plastik** application must be clean and dry, free from all kinds of dirt, oil and dust. The old paints must be scraped and removed. The cracks on the wall must be filled with paste. It can be applied either with brush or roller at min. +5°C. max + 30°C temperature.

Thinning (Volume)

To be thinned with 30% of water for the first layer, and 25% for the second. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

Drying Period (20°C)

Primary Drying: 15 minutes
Second Layer Application: 2 hours
Final drying: 24 hours
Becomes test resistant after: 4 days

Coverage

1 kg. of **Bianca Forza Plastik** covers 8 -10 m² a single dry film depending on the surface to be painted.

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

3,50 / 10,00 / 20,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.