

TECHNICAL DATA SHEET
Document No: TDS.SU.035

Revision Date / No: 26.10.2018 / 01



# **Forza Silicon Based Matt Paint**

Acrylic copolymer emulsion based, decorative topcoat wall paint for interior and exterior surfaces with mat appearance, deep white color and excellent covering capability.

## Areas of Use

An ideal plastic paint to be used successfully on the previously painted and non-faded surfaces, interior and exterior walls covered with plaster concrete, brick, fiberboard, wood and other similar construction materials.

#### **Specifications**

- Forza Silicone Based Matt Paint is an interior surface wall paint provides both saving and desired quality.
- Improved by silicone technology.
- Water based, with high respiration capability.
- · Complete fitness with the applied surfaces; no cracking, no blistering and no spilling.
- Non-faded due to its qualified pigment structure, with deep white color and excellent covering capability.
- Time and labour saving bound to high spreading power during the application.
- · Gives mat and smooth appearance to the surfaces with its carefully selected colors and high quality.
- Gives no disturbing odor during the application.

## Application

The surfaces subject to *Bianca Forza Matt Plastic Paint* application must be clean and dry, free from all kinds of dirt, oil and dust. The old paints must be scraped and removed. The cracks on the wall must be filled with paste. It can be applied either with brush or roller at min. +5°C max. +30°C temperature.

## Thinning (Volume)

To be thinned with 30 % of water for the first layer, and 25% for the second. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

#### Drying Period (20°C)

Primary Drying: 1/2 hours

Second Layer Application: 2 hours

Final drying: 24 hours

Becomes test resistant after 4 days.

### Coverage

1 liter of Bianca Forza Mat Plastik covers 8-10 m<sup>2</sup> a single dry film depending on the surface to be painted.

#### Coverage

Shelf life is 2 years when stored unopened, dry and cool conditions.

#### **Packing**

3,50 / 10, 00 / 20,00 kg

#### Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.