

TECHNICAL DATA SHEET

Document No: TDS.SU.037 Revision Date / No: 01.10.2018 / 00



Forza Ceiling Paint

Acrylic copolymer based, decorative, economical topcoat emulsion ceiling paint interior and exterior surfaces with mat appearance, white color and covering capacity.

Areas of Use

Interior surfaces, walls and ceiling, previously painted and new surfaces, plaster, brick and concrete surfaces.

Specifications

- Water based substance with high respiration capability.
- With mat and smooth appearance, it does not shine under light.
- Very high covering capability.
- No blistering and no spilling
- Time and labor saving bound to its spreading power during application.

Application

The surfaces subject to *Bianca Forza Ceiling Paint* application must be clean, dry and strong, free from all kinds of dirt, oil and dust. The old paints must be scraped and removed. The cracks on the wall must be filled with putty. It can be applied either with brush or roller at min. +5°C, max. +30°C temperature.

Thinning (Volume)

To be thinned with 30 % water for the first layer, and 25 % for the second. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

Drying Period (20°C)

Primary Drying: 15minutes

Second Layer Application: 2 hours

Final Drying: 24 hours

Becomes test resistant after: 4 days

Coverage

1 kg of *Bianca Forza Ceiling Paint* covers 8 - 9 m² a single dry film depending on the surface to be painted.

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

3,50 / 10,00 / 17,50 / 20,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.