



## Import Plastic - Wall Paint

Acrylic copolymer emulsion based decorative topcoat wall paint for interior and exterior surfaces, with mat appearance, Has a deep white color and excellent covering capability.

### Areas of Use

An ideal plastic paint to be used successfully on the previously painted or new and clear surfaces, interior and exterior walls covered with plaster concrete, brick, ytong, fiberboard, wood and other similar construction material.

### Specifications

- **Bianca Import Plastic** is an interior surface wall paint which provides both economy and desired quality.
- Water based, with high respiration capability.
- Complete fitness with the applied surfaces; no cracking, no blistering and no spilling.
- Non-faded due to its qualified pigment structure, with deep white color and excellent covering capability.
- Provides time and labour saving bound to high spreading power during the application.
- Gives mat and smooth appearance to the surfaces with its carefully selected colors and high quality.
- Gives no disturbing odor during the application.

### Application

The surfaces subject to **Bianca Import Plastic** application must be clean and dry, free from all kinds of dirt, oil and dust. The old paints must be scraped and removed. The cracks on the wall must be filled with paste. It can be applied either with brush or roller at min. +5°C max. +30°C temperature.

### Thinning (Volume)

To be thinned 30 % with water for the first layer, and 25 % for the second layer. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

### Drying Period (20°C)

First Drying: 1/2 hours  
Second Layer Application: 2 hours  
Final drying: 24 hours  
Becomes test resistant after 4 days

### Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 10 - 12 m<sup>2</sup>.

### Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

### Packing

0,75 / 2,50 / 7,50 / 15,00 lt

### Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.