

TECHNICAL DATA SHEET

Document No: TDS.SU.042
Revision Date / No: 01.10.2018 / 00



Isolation Primer

Water based, acrylic copolymer silicone paint primer and isolation material.

Areas of Use

Applicable on all kinds of plaster, concrete, satin casting, special kind of eternite plate surfaces.

Specifications

- Water preservation capability due to silicone structure.
- Prevents water leakage in the lavatories and bathrooms.
- Lowers the absorption capacity of the surfaces on finished walls, plaster, satin casting or pasted surfaces and reduces the paint consumption.
- Enables the well sticking of the paint on the surface by reinforcing the existing old paints.

Application

The surfaces subject to *Bianca Isolation Primer* application must be clean and dry, free from all kinds of dirt, oil and dust. It can be applied either with brush or roller at min. +5°C, max +30°C.

Thinning (Volume)

- 100 % thinned with water for the first layer if used as an isolation material. For the second and third layers, it may be thinned on half and half bases.
- Used as paint primer; thinned five times more with water before applying to surfaces.
- Used as satin plaster primer material in highly absorbent surfaces; thinned seven times more with water.

Drying Period (20°C)

First Drying: 15 minutes Final drying: 2 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 25 - 40 m².

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

0,75 / 2,50 / 7,50 / 15,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.