



Anti-Slip Floor Solution ZS-20

Thanks to its special formula, it is a solution that provides anti slip resistance on the ceramic surfaces.

Areas of Use

By using our **Bianca Anti-Slip Floor Solution** product on your tile floors, steps, concrete floors, outdoor wood end ecks, ramp sand drive ways, you can make your residential, commercial or industrial floor snon-slip and safer.

Specifications

- Effective for a long time.
- Can be User Indoors or Outdoors.
- Microscopicall yetches an invisible tread on any hard mineral surface.
- Makes the floor slip-resistant.

Application

The surfaces subject to paint application, must be clean and dry, free from all kinds of dirt, oil and dust, as well as old paint remainders. It is applied with a brush or roller to penetrate the surface exactly and equally well. **Bianca Anti-Slip Floor Solution** applied to the surface thinly. The applied surface dries within minutes and the process is completed. Optionally, two layers can be applied to increase performance.

Thinning (Volume)

Ready to use.

Coverage

With 1 liter, 20-22 m² area can be applied as a single coat..

Storage

Shelf life of the product is 1 year in its original can with the lid unopened.

Packing

5,00 / 20,00 lt

HazardStatements

- AcuteTox. (Swallowing) 3; H301: Toxic if swallowed.
- Skin Irritation 1B; H314: Causes severe skin burn sand eye damage.

Precautionary Statements

- Precautions

P260: Do not breathe dust / fumes / gas / mist / vapours / spray.

P264: Wash ...thoroughly after handling.

P280: Wear protective gloves / protective clothing / eye protection / face protection.

- Intervention

P301+310: IF SWALLOWED: Immediately call a POISON CENTER / doctor /...

P321: Specific treatment (see ...on this label).

- Disposal

P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste." Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

Warning Word

Danger

Hazard Signs

