



Panel Door Paint

It is a water based, acrylic emulsion resin based, semi-dull appearance, covering and protective refinish designed for American panel doors.

Areas of Use

It is used as a decorative refinishing paint used in new or previously painted American panel doors, wooden panel doors, mdf and solid wood surfaces.

Specifications

- Nonodorous as it is Solvent free and thinned with water.
- It has the maximum resistance against yellowing.
- It is resistant to water and domestic cleaning agents.
- It is not harmful to environment and human health.
- It ensures perfect adhesion to the application surface.
- It does not have a disturbing odour during application.

Application

Application surfaces must be dry, oil free, clean, cleaned from loose and swollen paint layers, surface correction treatment must be made if necessary. No paint should be applied on wet surfaces under any circumstance. It must be rubbed slightly and rubbing dusts must be removed from the surface. It must be paid attention that surface and ambient temperature is between +5°C and +30°C during application. Application can be made with a brush, roller and paint blaster. It must be thinned with water by 10%. While applying with a roller and brush 2 layers of paint are applied. It must be waited for 4-5 hours between the applications.

Thinning (Volume)

While applying with a brush, roller and paint blaster, it is thinned with water by 10%. Mix the paint before use and never mix it with a paint in another brand.

Drying Period (20°C)

Touch Drying: 30 - 40 minutes.
Set Drying: 24 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 10 - 15 m².

Storage

It is 2 years in an unopened original container at ambient temperature.

Packing

0,75 / 2,50 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.