



Silicon Based Exterior Primer

Silicone emulsion based exterior primer (white) with surface filling power.

Areas of Use

Applicable on the mineral based highly absorbent surfaces and also can be used before the first painting.

Specifications

- Forms a link between the paint and the surface.
- Reduces the paint consumption.
- Prevents water and moisture penetration in great scale.
- Prevent the generation of moss and bacterium.
- Prevents differential absorption of the paint by the surface.
- Increases the durability of the paint.

Application

The surfaces subject to **Bianca Silicon Based Exterior Primer (White Primer)** application must be clean and dry, free from all kinds of dirt, oil and dust. **Bianca Silicon Based Exterior Primer** is applied as a single layer either with brush, roller or spraying. **Bianca Silicon Based Exterior Paint** is used 6 hours after the application of **Bianca Silicon Based Exterior Primer**. Attention should be given to the temperature of the surface and the atmosphere during the application, preferably to be kept at min. +5°C, max +30°C.

Thinning (Volume)

At most 10 % thinned with water.

Drying Period (20°C)

Last Layer Paint Application: 6 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 12 - 14 m².

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

2,50 / 7,50 / 15,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.