



Ceiling Paint

Acrylic copolymer based, decorative emulsion topcoat ceiling paint for both interior and exterior surfaces with mat appearance, has a deep white color and excellent covering capacity.

Areas of Use

Interior surfaces, walls and ceiling, previously painted or new and clean surfaces, plaster, brick and concrete surfaces.

Specifications

- Water based substance with high respiration capability.
- With mat and smooth appearance, it does not shine under light.
- Very high covering capability.
- No blistering and no spilling.
- Time and labor saving bound to its spreading power during application.

Application

The surfaces subject to **Bianca Ceiling Paint** application must be clean, dry and strong, free from all kinds of dirt, oil and dust. The old paints must be scraped and removed. The cracks on the wall must be filled with putty. It can be applied either with brush or roller at min. +5°C, max. +30°C temperature.

Thinning (Volume)

To be thinned 20 % with water for the first layer, and 15 % for the second layer. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

Drying Period (20°C)

First Drying: 15 minutes
Second Layer Application: 2 hours
Final Drying: 24 hours
Becomes test resistant after: 4 days.

Coverage

Depending on the application and the surface, for single layer, 1 kg will be enough to cover the 9 - 10 m².

Depolama

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

1,00 / 3,50 / 10,00 / 17,50 / 20,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.