



Tegola - Roofing Tiles Paint

Acrylic emulsion based exterior topcoat paint.with high resistant to UV ray.

Areas of Use

Applied successfully on exterior surfaces of all kinds of construction elements such as plastered concrete, ytong, brick and eternite walls for decorative and isolation purposes.

Specifications

- It has an excellent concealing feature.
- It does not fade, crack, swollen and flake.
- Provides extraordinary protection against harmful effects UV rays in sunlight with its UV resistant colours.
- Resistant to atmospheric conditions and pollution, sunlight, friction and impacts.
- Easy to apply and saves time and labour thanks to high diffusion on surface.
- It brings an opaque appearance to facades with its specially chosen colours and high quality.
- Does not have a disturbing smell during application.

Application

The surfaces subject to **Bianca Tegola - Roofing Tiles Paint** application, must be clean and dry, free from all kinds of dirt, oil and dust, as well as old paint remainders. The temperature of the surface and the surroundings must be min +5°C, Max +30°C. Applied as a single layer either with brush or roller availing the complete and equal penetration of the paint into the surface. In order to prevent streaky movements on the wide surface, the material should always be thinned with same amount of water, thoroughly mixed, and be applied without break. There should be no extreme wind or air circulation in the application area.

Thinning (Volume)

With brush and roll to be thinned up to 20 - 25 % with water for both layers. thinner with 30 - 40% water in applications with airless spray system. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

Drying Period (20°C)

First Drying: 15 minutes
Second Layer Application: 2 hours
Final drying: 24 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 4 - 6 m².

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

15,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.