

TECHNICAL DATA SHEET
Document No: TDS.SU.062

Revision Date / No: 01.10.2018 / 00



# **Silicon Based Interior & Exterior Universal Primer**

Silicone emulsion based interior and exterior white primer with surface filling power.

# Areas of Use

Applicable on the mineral based highly absorbent surfaces and also can be used before the first painting.

## **Specifications**

- Forms a link between the paint and the surface.
- Reduces the paint consumption.
- Prevents water and moisture penetration in great scale.
- Prevents differentail absorption of the paint by the surface.
- Increases the durability of the paint.

#### Application

The surfaces subject to *Silicon Based Interior & Exterior Universal White Primer* application must be clean and dry, free from all kinds of dirt, oil and dust. *Silicon Based Interior & Exterior Universal White Primer* is applied as a single layer either with brush, roller or spraying. Make sure that the temperature of the surface and the atmosphere during the application, is between. +5°C, and +30°C.

## Thinning (Volume)

Thinned with at most 20% of water.

## Drying Period (20°C)

Last Layer Paint Application: 6 hours.

#### Coverage

Depending on the application and the surface, for single layer, 1 kg will be enough to cover the 12 - 14 m<sup>2</sup>.

#### Storage

Shelf life of theproduct is 2 years in itsoriginal can withthelidunopened.

#### Packing

3,50 / 10,00 / 20,00 kg

### Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.