

TECHNICAL DATA SHEET
Document No: TDS.SU.065

Revision Date / No: 01.10.2018 / 00



Vals Silk Matt (Silicone - Cleanable Wall Paint)

Water based, decorative indoors finish paint with silicon additives, with high fade resistance, and with a silk matt texture.

Areas of Use

It can be applied on satin plastered or pasted interior surfaces, wall board, wooden surfaces and also used in restoration and decoration of places such as hotels, hospitals, schools, restaurants, children rooms etc.

Specifications

- High quality performance against friction and washing.
- Gives silk matte texture and smooth appearance to the surfaces.
- Water based substance with high respiration capability.
- Complete fitness with applied surfaces, no cracking, no blistering, no spilling.
- Non-faded due to its qualified pigment structure, with deep white color and excellent covering capacity.
- Time and labor saving bound to high spreading power during application.
- Gives no disturbing odor during the application.

Application

The surfaces subject to *Bianca Vals Silk Matt* must be clean and dry free from all kinds of dirt, oil and dust. The old paints must be scraped and removed. The surface of the wall must be smoothed with satin plaster or sized paste. The surface smoothed must be left for drying at least 24 - 48 hrs. The scrapes on the surface must be removed with a sandpaper. After the preparation of the surface, *Bianca Vals Primer* is applied. *Bianca Vals Primer* is applied as a single layer without diluting and left to dry for 24 hours. *Bianca Vals Silk Matt* is applied on the surface in two layers with a roll, brush or through spraying. Care should be taken to ensure that during application, the surface and the ambient temperature should be between +5°C and +30°C.

Thinning (Volume)

Dilute with 10 % water and apply in two coats. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

Drying Period (20°C)

Touch-dry: 15 minutes Dust Free: 1 hour

Second Coat Application: 6 hours Thorough Drying: 24 hours

Becomes test resistant after 3 days.

Coverage

1 liter of Bianca Vals Silk Matt covers 16 - 17 m² a single dry film depending on the surface to be painted.

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

0,75 / 2,50 / 7,50 / 12,00 / 15,00 lt



TECHNICAL DATA SHEET

Document No: TDS.SU.065
Revision Date / No: 01.10.2018 / 00

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.