



## Vals Passing Primer

Acrylic copolymer emulsion based white interior primer.

### Areas of Use

Surfaces previously painted with water or solvent based paints that need change of color or decoration due to faded colors or dirtiness, and in general, applicable as an undercoat in all kinds of water based painting processes.

### Specifications

- Prevents water and moisture penetration in great scale.
- Prevents the generation of moss and bacterium.
- Prevents differential absorbtion of the paint by the surface.
- By penetration into the inner layers of the applied surface, provides complete fitness with the paint which will come over it.
- Enables well spreading of the paint on the surface thus reducing the paint consumption due to its rapid drying in hot weathers and anti-absorbent nature.

### Application

The surface must be clean and dry. It must be prepared by restoring blistered and spilled parts by a filling system. Particularly, the surfaces been applied solvent based oil paint must be scrapped and the oxidation layer must completely be removed and only after cleaning of the dust, the undercoating must be applied. It is applicable to the surface as a single layer either with brush, roller or spray method. The temperature must be min. +5°C, during the application.

### Thinning (Volume)

At most 10% to be thinned with water.

### Drying Period (20°C)

Final Layer Paint Application: 24 hours

### Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 10 - 12 m².

### Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

### Packing

2,50 / 7,50 / 15,00 lt

### Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.