



Vista Silicon Special Matt

Acrylic copolymer emulsion based topcoat decorative wall paint for interior and exterior surfaces, with mat appearance, Has a deep white color and excellent covering capability.

Areas of Use

An ideal plastic paint to be used successfully on the previously painted or new and clear surfaces, interior and exterior walls covered with plaster concrete, brick, fiberboard, wood and other similar construction materials.

Specifications

- **Vista Plastic** is an interior surface wall paint which provides both economy and desired quality.
- Improved by silicone technology.
- Water based, with high respiration capability.
- Complete fitness with the applied surfaces ; no cracking, no blistering and no spilling.
- Non-fading due to its qualified pigment structure, with deep white color and excellent covering capability.
- Provides time and labour saving bound to high spreading power during the application.
- Gives mat and smooth appearance to the surfaces with its carefully selected colors and high quality.
- Gives no disturbing odor during the application.

Application

The surfaces subject to **Vista Plastic** application must be clean and dry, free from all kinds of dirt, oil and dust. The old paints must be scraped and removed. The cracks on the wall must be filled with paste. It can be applied either with brush or roller at min. +5°C and max. +30°C temperature.

Thinning (Volume)

To be thinned with 30 % of water for the first layer, and 25 % for the second layer. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

Drying Period (20°C)

First Drying: 1/2 hours
Second Layer Application: 2 hours
Final drying: 24 hours
Becomes test resistant after: 4 days

Coverage

Depending on the application and the surface, for single layer, 1 kg will be enough to cover the 8 - 10 m².

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

3,50 / 10, 00 / 20,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.