

TECHNICAL DATA SHEET

Document No: TDS.SL.001

Revision Date / No: 01.10.2018 / 00



Wood Stain

Synthetic alkyd resin based, decorative wood protector.

Areas of Use

Can be applied on allkinds of interior and exterior wooden surface sespecially which are subject to atmospheric air effects, doors, window frames, furniture with natural appearance and wood works.

Specification

- Good protection against microorganisms, insects, mildew.
- Penetrates deeply in wood due to excellent penetration power.
- Perfect resistant to UV rays.
- Fast drying, moisture adjusting.
- Perfect working properties.
- Gives a decorative and uniformeffect.

Application

All wood surfaces must be free of oil, paint, grease and dirt. Apply impregnation care to have excellent protection for new wood surfaces. Apply 2 coats of *Bianca Wood Stain*. Wait for 24 hours between respective coatings. It can be applied at min. +5°C, max. +30°C temperature.

Thinning (Volume)

Definitely do not dilute. Stir thoroughly before the application.

Drying Period (20°C)

Hardening: 12 hours Recoatable: 24 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 10 - 15 m².

Flash Point

38°C

Storage

Shelf life is 2 years when stored unopened, dry and cool conditions.

Packing

0,75 / 2,50 / 15,00 lt

Hazard Classification

- Flame. Liquid 2, H225: Highly flammable liquid and vapor.
- Asp. Toxicity 1, H304: Fatal if enters airways and swallowed.

Precautionary Statements

-Precautions

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P240: Ground / bond container and receiving equipment.

P241: Use explosion-proof electrical / ventilating / light equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.



TECHNICAL DATA SHEET
Document No: TDS.SL.001

Revision Date / No: 01.10.2018 / 00

P280: Wear protective gloves / protective clothing / eye protection / face protection.

-Intervention

P301+310: IF SWALLOWED: Immediately call the National POISON CENTER at Phone No: 114 or a doctor / physician.

P303+361+353: ON CONTACT WITH SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.

P331: DO NOT induce vomiting.

P370+P378: In case of fire: Use alcohol, foam, dry chemicals and carbon dioxide to extinguish.

-Storage

P403+235: Store in a well ventilated place. Keep cool.

P405: Store locked up.

-Disposal

P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste." Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

Warning Word

Danger

Hazard Signs



