



## Bia-Prime Gloss

### Special Primer For Glossy And Non-Absorbent Surfaces

**Bia-Prime Gloss** is a primer for single-use ready-to-use, glossy and non-absorbent surfaces with a combination of special acrylic polymer and epoxy resin.

#### Areas of Use

- Indoors and outdoors.
  - On the wall and on the ground.
  - Ceramic adhesives, ground self leveling, as a primer before applications.
  - It is used as a primer before the repair mortars applications.
- Ceramic, paving stones, terrazo, enamelled engineering bricks, natural and cast stones that have the impermeable nonabsorbent surfaces.

#### Advantages

- Ready to use.
- Easy to prepare and apply.
- It does not contain solvent, it does not harm the environment and the applicator,
- Excellent adhesion to the floor and the next coat,
- It is colored in yellow for control purposes and is noticed on the applied surface.

#### Technical Specifications

<b>Structure of Material</b>	: Modified special polymer Dispersion and Epoxy Resin
<b>View</b>	: Liquid Light yellow
<b>Density</b>	: 1,2 kg/l.
<b>Drying Time</b>	: 3 hours

#### Preparation of Surface

The surfaces to be applied must be free from all kinds of residues such as paint, oil, asphalt. Care should be taken that the floor is dry.

#### Mixing

The material should be mixed with a 400 - 600 rpm mixer tip drill for at least 3 minutes until a homogeneous mixture is obtained.

#### Application

The material is poured directly onto the surface and spread with a soft bristle brush crosswise to the floor to ensure that there is no untreated area. Other applications are made on the floor of the material after full drying.

#### Consumption

It is recommended to use between 120 - 180 gr/m<sup>2</sup> depending on the surface condition.

#### Self Life

It is 6 months from the date of manufacture in the appropriate storage conditions.

#### Storage

It should be stored in original unopened package, in cool and dry environment, protected from freezing.

#### Packing

5,00 kg

### ***Security Precautions***

---

Application areas should be ventilated. During the application, it must be used, in accordance with the Occupational Health and, Safety, the work clothes, protective gloves, goggles. Due to the irritant effects of curing materials, the components should not come into contact with the skin and the pore, in case of contact with plenty of soap and washed, if swallowed, seek medical advice immediately. Application areas should be ventilated and food and drinks stuffs should not be put into application areas. It should be stored at places where children can not reach it. For detailed information safety data sheet (Material Safety Data Sheet).

### ***Responsibility***

---

The information given in this technical document is based on our scientific and practical knowledge. Orkim Ortaklar Boya Sanayi ve Pazarlama A.Ş. it is only responsible for the quality of the product. Orkim Ortaklar Boya Sanayi ve Pazarlama A.Ş. shall not be held liable for any consequences which may arise from outside of the written suggestions about where and how the product will be used and/or due to incorrect use. The responsibility of applying our product correctly is the responsibility of the user.