



Biancalite Exterior Primer (Transparent)

Transparent primer based on thermoplastic resins to consolidate exterior wall surface.

Areas of Use

All kinds of interior and exterior walls, masonry concrete, plaster, gypsum, plastic and synthetic surfaces.

Specification

- Forms a link between the paint and the surface.
- Reduces the paint consumption.
- Prevents water and moisture penetration in great scale.
- Prevents the generation of moss and bacterium.
- Prevents differential absorption of the paint by the surface.
- Increases the duration period of the paint.
- It can be applied all kinds of climate .
- Application directly on damped and wet surfaces possible.

Application

The surfaces subject to **Biancalite Transparent Exterior Primer** application must be clean and dry, free from all kinds of dirt, oil and dust. **Biancalite Transparent Exterior Primer** is applied as a first layer either with brush, roller or spraying. Topcoat paint is used 18 hours after the application. All kinds of emulsion or solvent based exterior covering, synthetic or emulsion paste can be applied over **Biancalite Transparent Exterior Primer**.

Thinning (Volume)

Use without thinning.

Drying Period (20°C)

Final Layer Paint Application: 18 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 8 – 14 m².

Flash Point

41°C

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

15,00 lt

Hazard Classification

- Flame. Liquid 3, H226: Flammable liquid and vapor.
- Asp. Toxicity 1, H304: Fatal if enters airways and swallowed.
- BHOT Tek. Mrz. 3, H336: May cause drowsiness and dizziness.
- Carcinogen 1B; H350: May cause cancer (carcinogenic).
- Aquatic Chronic 2, H411: Toxic to aquatic life with long-lasting effects.

Additional Hazard Information Statements

- EUH066: Could cause dryness and cracking of skin upon repeated exposure

Precautionary Statements

-Precautions

- P201: Read special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground / bond container and receiving equipment.
P241: Use explosion-proof electrical / ventilating / light equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P261: Avoid breathing dust / fumes / gas / mist / vapors / spray.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves / protective clothing / eye protection / face protection.
P281: Use Personal Protective Equipment

-Intervention

- P301+310: IF SWALLOWED: Immediately call the National POISON CENTER at Phone No: 114 or a doctor / physician.
P304+340: IF INHALED: Remove person that is exposed to fresh air and keep comfortable for breathing.
P303+361+353: ON CONTACT WITH SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
P308+313: IF exposed or under effect: obtain medical attention / treatment
P312: IF you feel unwell: Call the National POISON CENTER at phone no. 114 or the doctor / physician.
P353: Rinse skin with water / shower
P370+P378: In case of fire: Use alcohol, foam, dry chemicals and carbon dioxide to extinguish.
P391: Collect spillage.

-Storage

- P403+233: Store in a well ventilated place. Keep container tightly closed.
P403+235: Store in a well ventilated place. Keep cool.
P405: Store locked up.

-Disposal

- P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste."
Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

Warning Word

Danger

Hazard Signs

