



Bis-Kes - Soot & Stain Covering Paint

Alkyd resin based interior and exterior topcoat which prevents stains from coming back to the surface by perfectly covering smoke and fire stains such as nicotine, oil, moisture, ink, pen, lipstick on the surfaces.

Areas of Use

It can be easily applied to any painted or unpainted surface (wall / ceiling) on interior and exterior walls.

Specification

- It has high adhesion and wearing resistance.
- Dries very fast.
- It is not subject to discoloration in time.
- It is a matte paint.
- Resistant to moisture stains, molds and spills.
- Prevents the surface from coming back up by closing the stains perfectly.

Application

Application surfaces must be dry, oil free, clean, cleaned from loose and swollen paint layers, surface correction treatment must be made if necessary. No paint should be applied on wet surfaces under any circumstance. It must be rubbed slightly and rubbing dusts must be removed from the surface. It must be paid attention that surface and ambient temperature is between +5°C and +30°C during application. Application can be made with a brush, roller and paint blaster. It must be thinned with cellulosic thinner by 10%. While applying with a roller and brush 2 layers of paint are applied. It must be waited for 24 hours between the applications.

Thinning (Volume)

Ready for use. If necessary, it is thinned with cellulosic thinner. Stir thoroughly before using the paint and do not mix it with a paint of other brands.

Drying Period (20°C)

Touch Drying: 15 minutes
Anti-Dust Retention: 30 minutes
Set Drying: 1 - 2 hours

Coverage

Depending on the application and the surface, for single layer, 1 kg will be enough to cover the 6 – 8 m².

Flash Point

21°C

Storage

It is 2 years in an unopened original container at ambient temperature.

Packing

0,25 / 0,50 / 1,00 / 3,00 / 20,00 kg

Hazard Classification

- H226: Flammable liquid and vapor.
- H304: Fatal if enters airways and swallowed..

Precautionary Statements

- Precautions

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical / ventilating / light equipment.

P243: Take precautionary measures against static discharge.

P280: Wear protective gloves / protective clothing / eye protection / face protection.

- Intervention

P301+310: IF SWALLOWED: Immediately call the National POISON CENTER at Phone No: 114 or a doctor / physician.

P331: DO NOT induce vomiting.

P370+P378: In case of fire: Use alcohol, foam, dry chemicals and carbon dioxide to extinguish.

- Storage

P403+235: Store in a well ventilated place. Keep cool.

- Disposal

P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste."

Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

Warning Word

Danger

Hazard Signs

