



Matt Parquet Varnish

Urethane alkyd based, single component matt varnish for parquets.

Areas of Use

Applicable on all types of parquet.

Specification

- High and long lasting gloss sheen.
- Transparent.
- Forms a thick film.
- Resistant to detergents and other home cleaning materials.

Application

Surfaces to be polished should be scraped and any dirt or dust should be removed. Any stains, oil, etc. should be washed using detergent water or chemicals and dried. Apply one coat of the polish as primer to avoid tarnishing of scraped surfaces. Primed surfaces can be polished later on, if desired. Wait for 5 - 6 hours between each coat application. If a period longer than 24 hrs has elapsed slightly sand and clear the surface. Minimum temperature for application is +10°C.

Thinning (Volume)

To be thinned with 10 % of synthetic thinner. Stir thoroughly before application.

Drying Period (20°C)

Set to touch: 2 –3 hours
Dust repelling: 5 – 6 hours
For sanding: 10 hours
Walk upon: 24 hours
Hardening: 72 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 10 – 14 m².

Flash Point

38°C

Storage

Shelf life is 2 years when stored unopened, dry and cool conditions.

Packing

0,75 / 2,50 / 12,00 lt

Hazard Classification

- Flame. Liquid 3, H226: Flammable liquid and vapor.
- Asp. Toxicity 1, H304: Fatal if enters airways and swallowed.
- Skin Irritation 2 H315: Causes skin irritation
- BHOT Repeated Exposure2, H372: Causes damage to organs through prolonged or repeated exposure.
- BHOT Repeated Exposure3, H336: May cause drowsiness or dizziness.
- Aquatic Chronic 2, H411: Toxic to aquatic life with long-lasting effects.

Precautionary Statements

Orkim Ortaklar Boya Sanayi ve Pazarlama A.Ş. Karaağaç Mah. Hadımköy İstanbul Caddesi No: 36 Büyükçekmece - İstanbul
Tel: +90 (212) 858 16 00 (pbx) Faks: +90 (212) 858 04 08 www.biancaboya.com info@biancaboya.com

-Precautions

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground / bond container and receiving equipment.
P241: Use explosion-proof electrical / ventilating / light equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe dust / fumes / gas / mist / vapors / spray.
P261: Avoid breathing dust / fumes / gas / mist / vapors / spray.
P264: Wash thoroughly with soap and water after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves / protective clothing / eye protection / face protection.

-Intervention

P301+310: IF SWALLOWED: Immediately call the National POISON CENTER at Phone No: 114 or a doctor / physician.
P302+352: IF ON SKIN: Wash with plenty of water and soap.
P303+361+353: ON CONTACT WITH SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
P304+340: IF INHALED: Remove person, if having difficulties in breathing, to fresh air and keep comfortable for breathing.
P312: Call a POISON CENTER/ doctor / physician if you feel unwell.
P314: Get Medical advice / attention if you feel unwell.
P321: Specific treatment is required (see the label)
P331: DO NOT induce vomiting.
P332+P313: If skin irritation occurs: Get medical advice / attention.
P362: Take off and wash prior to use any contaminated clothing.
P370+P378: In case of fire: Use alcohol, foam, dry chemicals and carbon dioxide to extinguish.
P391: Collect spillage.

-Storage

P403+235: Store in a well ventilated place. Keep cool.
P405: Store locked up.

-Disposal

P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste."
Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

Warning Word

Danger

Hazard Signs

