Silicon Based Decorative Coating Primer

A white coloured silicon emulsion based coating primer with high adherence property.

Areas of Use

Is applied before final coating on heat insulation systems, or either exterior and interior surfaces no matter whether is it painted before or not.

Specifications

- Highly adherent.
- High degree water and moisture-proof.
- Provides a strong bond between the surface and the coating.
- Inhibits the appearance of stains on old surfaces.
- Highly covering white coloured.
- Stiffens the surface and decreases the absorbance.

Application

The surface ***Bianca Silicon Based Coating Primer*** is to be applied on has to be clean and dry. If the had been covered with a solvent based paint it should also be removed. İf the surface used to be painted with an emulsion based paint or is painted for the first time ***Bianca Silicon Based Coating Primer*** can be applied directly by mans of a brush any other method. Mix before the use, The air and surface temperature at the moment of application has to be between +5ºC and+30ºC. Refrain from application if the weather is too windy or too hot. We recomend to wait 1 day before passing to the application of ***Bianca Decorative Coating***.

Thinning (Volume)

Produced as ready-to-use. In case of necessity can be diluted up to 10%.

Drying Period (20°C)

First Drying: 1 hour
Final drying: 24 hours
The application of mineral coating can be performed 24 hrs after.

Coverage

1 liter of the product can be applied to 12-14 m² area in single layer. This characteristic may change according to the application method and surface type.

Storage

Can be stored in unopened package for 2 years in dry and cool conditions.

Packing

25,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.