

TECHNICAL DATA SHEET
Document No: TDS.YK.018

Revision Date / No: 29.04.2020 / 01



Grout Protector

Acrylic emulsion based grout protection

Contributing to the preservation and long life of colored grout fillings.

Application Area

It is used to protect the color of the colored grout filling applied on the surfaces and floors that are frequently cleaned, such as kitchen counter and benches, and to ensure long life.

Application Surface

- In indoors and outdoors;
- · On to the grouting.
- Consult us for all the other application surfaces.

Application Border

It is not a long lasting and proper solution over the applying on worn, low strength groutings.

Warnings and Recomendations

While the *Bianca Grout Protector* is applied, it should not be carried out of the grouts and if it has a part that overflows, it should be cleaned absolutely without drying.

Surface Preparation

Prior from the application of Bianca Grout Protector, grouts must be cleaned from dust.

Application Condition

Ambient temperature is between the +5°C and +30°C. It should be avoided from the application in very humid and / or very hot weather.

Application

At least 48 hours after application of grouting, it is applied to the grouts with a brush as 2 coats with 1 hour interval, without being diminished .

Consumption

20 ml/m²

Packing

1,00 It

Color

Transparent

Application Tools

Sponge, lambskin roller, silim machine.

Shelf Life

It is 5 years from the date of production provided that the mouth of the packaging is not opened in dry and cool environment. When not in use, the mouth of the packaging should be tightly closed. Packages must be protected from frozen.