

TECHNICAL DATA SHEET
Document No: TDS.DYS.003

Revision Date / No: 29.01.2019 / 00



Silicon Based Exterior Jamb Paint

Acrylic copolymer emulsion based decorative exterior paint, dirt repellent, with silicone additive, silk mat appearance. which preserves its elastic feature even -30° C..

Areas of Use

Window frame, plaster, concrete, mineral surfaces, also used for decorative purposes to make designs on the deformed plastering and defective surfaces.

Specifications

- Non-oxidizing, resistant to salt, moisture and weak chemical solvents.
- Prevents the generation of bacterium.
- Resistant to ultra-violet rays.
- Can be washed surface detergent or soaped water.
- Silk-mat appearance.
- Does not loose its elastic nature within time.
- Hides the very fine cracks due to its elastic nature.
- Enables to work out various designs on the applicable surface by change of roller.
- Walls continuously remain dry due to its water-repellent nature. By this way, the loss of heat, surface pollution, formation of moss and mold is minimized.

Application

Applicable surfaces must be clean and dry, free from old painting remains, all kinds of dirt, oil and dust. **Bianca Silicone Based Exterior Primer (White Primer)** must be applied to the highly absorbent surfaces that are to be painted for the first time. At least 6 hours should pass after the application of the primer. Then **Bianca Silicone Based Exterior Jamb Paint** should be applied.

Thinning (Volume)

Thinned with water for both layers up to 15 %. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

Drying Period (20°C)

Final Drying: 2 - 6 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 10 - 12 m².

Storage

Shelf life of the product is 2 years in its original can with the lid unopened.

Packing

15,00 lt

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.