# **d**bianca

# TECHNICAL DATA SHEET Document No: TDS.SL.019 Revision Date / No: 01.10.2018 / 00



# Forza Rapid Industrial Primer

Alkyd resin based, air dried primer paint used for industrial purposes.

#### Areas of Use

It is used for painting surfaces such as any kinds of machinery, agricultural, work and garden machines, tractor, trailer, automobile radiator assembly, barrel, valve, steel items and water pumps.

### Specification

- It is a primer paint containing anticorrosive pigments
- Does not cause brush mark and pouring
- · Good adhesion onto the metal surfaces.
- Provides a smooth surface for Rapid refinish
- Resistant to short term lean impacts.
- It dries fast.

#### Application

The application surface must be cleaned form dust with sand blasting or sandpapering. The metal surface is cleaned from dirt, dust, oil and etc. The primer, thinned by 10-15% with rapid thinner, is applied with paint gun. The primer must be stirred well before use. It is recommended to apply *Bianca Forza Rapid Industrial Paint* to the surfaces on day after *Bianca Forza Rapid Industrial Primer* is applied.

#### Thinning (Volume)

To be thinned with 10-15 % of rapid thinner

#### Drying Period (20°C)

Touching period: 10 - 20 minutes Anti-dust period: 2 - 3 hours Full drying: 24 hours

#### Coverage

Depending on the application and the surface, for single layer, 1 kg will be enough to cover the  $7 - 10 \text{ m}^2$ .

#### Storage

It is 2 years when stored under room temperature in unopened original container. Store between +5°C and +30°C.

#### Packing

0,75 / 3,00 / 15,00 kg

#### Hazard Classification

- Flame. Liquid 3, H226: Flammable liquid and vapor.
- Asp. Toxicity 1, H304: Fatal if enters airways and swallowed.
- BHOT Repeated Exposure 2, H373: May causes damage to organs through prolonged or repeated exposure.

#### **Precautionary Statements**

#### -Precautions

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical / ventilating / light equipment.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust / fumes / gas / mist / vapors / spray.

Orkim Ortaklar Boya Sanayi ve Pazarlama A.Ş. Karaağaç Mah. Hadımköy İstanbul Caddesi No: 36 Büyükçekmece - İstanbul Tel: +90 (212) 858 16 00 (pbx) Faks: +90 (212) 858 04 08 www.biancaboya.com info@biancaboya.com



# TECHNICAL DATA SHEET Document No: TDS.SL.019 Revision Date / No: 01.10.2018 / 00

P280: Wear protective gloves / protective clothing / eye protection / face protection. *-Intervention* 

P301+310: IF SWALLOWED: Immediately call the National POISON CENTER at Phone No: 114 or a doctor / physician.

P314: Get Medical advice / attention if you feel unwell.

P331: DO NOT induce vomiting.

P370+P378: In case of fire: Use alcohol, foam, dry chemicals and carbon dioxide to extinguish.

#### -Storage

P403+P235: Store in a well ventilated place. Keep container tightly closed.

#### -Disposal

P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste." Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

#### Warning Word

Danger

#### Hazard Signs

