



Import Synthetic

Synthetic alkyd resin based economical top coat paint with glossy appearance and excellent hiding power.

Areas of Use

All kinds of interior and exterior wood, metal surfaces and mineral substrates , together with appropriate primer.

Specification

- High and long lasting glossy appearance.
- Yellowing resistance.

- Excellent covering and expanding abilities.
- Easily applied by a brush.
- No brush prints no drips.
- Resistant to dust and dirt sticking.
- Resistant to mechanical damage and chemical detergents of home use.

Application

All surfaces must be sound, clean, dry, and free of substances, preventing adhesion. The old paints must be scraped and removed. The cracks on the wall must be filled with putty. It can be applied at min. +5°C, max. +30°C temperature.

A) Wood Surfaces: Apply **Bianca Wood Stain** in a single layer. After that if it is necessary apply synthetic putty. Sanding is recommended after this application. Then apply **Bianca Synthetic Primer** as a single layer. 12 hrs. later **Bianca Import Synthetic** can be applied in 2 layers 24 hrs. should elapse between the layer applications.

B) Metal Surfaces: Coat new metal surfaces with **Bianca Anti-Rust Primer** as a single layer. After that apply **Bianca Synthetic Primer** as a single layer .

Apply **Bianca Import Synthetic Gloss Paint** coat after 12 hours of priming by means of brush, roller or air less spraying equipment application, make 24 hrs. pause between the layer application.

Thinning (Volume)

10 – 15 % to be thinned with thinner. Stir thoroughly before using the paint and do not mix it with a paint of other brands.

Drying Period (20°C)

Set to touch: 2 hours
Dust repelling: 4 – 6 hours
Hardening: 24 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 15 – 20 m².

Flash Point

38°C

Storage

Shelf life is 2 years when stored unopened, dry and cool conditions.

Packing

0,25 / 0,75 / 2,50 / 15,00 lt

Hazard Classification

- Flame. Liquid 3, H226: Flammable liquid and vapor.
- Asp. Toxicity 1, H304: Fatal if enters airways and swallowed.
- BHOT Repeated Exposure 3, H336: May cause drowsiness and dizziness.
- Aquatic Chronic 2, H412: Harmful to aquatic life with long-lasting effects.

Additional Hazard Information Statements

- EUH066: Could cause dryness and cracking of skin upon repeated exposure.

Precautionary Statements

-Precautions

- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground / bond container and receiving equipment.
P241: Use explosion-proof electrical / ventilating / light equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P261: Avoid breathing dust / fumes / gas / mist / vapors / spray.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves / protective clothing / eye protection / face protection.

-Intervention

- P301+310: IF SWALLOWED: Immediately call the National POISON CENTER at Phone No: 114 or a doctor / physician.
P304+340: IF INHALED: Remove person that is exposed to fresh air and keep comfortable for breathing.
P303+361+353: ON CONTACT WITH SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
P312: IF you feel unwell: Call the National POISON CENTER at phone no. 114 or the doctor / physician.
P331: DO NOT induce vomiting.
P370+P378: In case of fire: Use alcohol, foam, dry chemicals and carbon dioxide to extinguish.

-Storage

- P403+233: Store in a well ventilated place. Keep container tightly closed.
P403+235: Store in a well ventilated place. Keep cool.
P405: Store locked up.

-Disposal

- P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste."
Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

Warning Word

Danger

Hazard Signs

