



## PU Exterior Coating Adhesive

Solvent free single component fast drying polyurethane adhesive.

### Areas of Use

Applied on joint points of styrofoam jambs and exterior decoration panels where cracks formation is possible.

### Specifications

- Highly Durable.
- Cures Rapidly.
- Expanding does perform the functions of a filler.
- Pres time – 2 hrs at 20 °C room temperature
- Becomes waterproof within 24 hrs after the application

### Application

Applied on the surface by means of a spatula or a brush as a thin film. Afterwards attached to the other surface without any gaps left. Slightly cleaned after 24 hrs and after that the surface is amended by **Bianca Elastic Fibred Plaster**.

### Storage

**Bianca Exterior Coating Adhesive** is to be stored in closed package in a dry place. Ideal storage temperature is 15 – 25°C. Considered these conditions preserved the shelf life of the product is 12 months with unopened can.

### Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.