



Ceramic Protector

Acrylic emulsion based ceramic protector

It prevents the coatings from getting dirty after application of colored grout.

Application Area

It is used to protect sensitive materials like stones such as granite, ceramic, natural stone, especially before dark grouting applications.

Application Surface

- In indoors and outdoors; in -Ceramic, -Granite ceramic, -Granite, natural composition stone and in the similar coating materials.
- Consult us for all the other application surfaces.

Application Border

It can never be applied to a dirty, greasy surfaces.

Warnings and Recomendations

When **Bianca Ceramic Protector** is applied, it should be worn gloves and avoided from the contact with eyes and skin.

Surface Preperation

The surface must be durable.

Application Condition

- Ambient temperature is between the +5°C and +30°C.
- It should be avoided from the application in very humid and / or very hot weather.

Application

- **Bianca Ceramic Protective** must be applied without diminishing with the help of a lambskin roller or a sponge, before the grouting application.
- After 10 minutes from the first layer, a second layer, **Bianca Ceramic Protector**, should be applied.
- After the surface has been left to dry for 10 minutes, it can be passed to the application of grouting.

Consumption

35 ml/m²

Packing

1,00 lt

Color

Transparent

Application Tools

Brush

Shelf Life

It is 2 years from the date of production provided that the mouth of the packaging is not opened in dry and cool environment. When not in use, the mouth of the packaging should be tightly closed. Packages must be protected from frozen.