

TECHNICAL DATA SHEET
Document No: TDS.SL.037

Revision Date / No: 01.10.2018 / 00



# **Varnish Based Wood Stain**

Synthetic alkyd resin based, one component, transparent, decorative wood protector.

#### Areas of Use

Can be applied on all kinds of interior and exterior wooden especially which are subject to atmospheric air effects, doors, window frames, furniture with natural appearance and wood works.

## Specification

- Good protection against micro organisms, insects, mildew.
- Let the surface breath.
- Does not need primer. It is easy to apply and is economic.
- Penetrates deeply in wood due to excellent penetration power.
- Perfect resistant to UV lights.
- Fast drying, moisture adjusting.
- With its special formula, keeping the natural and peculiar properties, it gives decorative appearance to the wood.

### **Application**

All wood surfaces must be free oil, paint, grease and dirt. Apply 2 - 3 coats of Bianca Varnish Based Wood Stain with brush or roller. Wait for 24 hours between respective coatings. It can be applied at min. +5°C, max. +30°C temperature.

### Thinning (Volume)

To penetrates deeply in wood, 25 - 30 % to be thinned with thinner first coat. Do not dilute for second and third coat.

# Drying Period (20°C)

Set to touch: 2 - 3 hours Dust Free: 3 - 4 hours Hardening: 24 hours

# Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 12 - 15 m<sup>2</sup>.

### Flash Point

38°C

### Coverage

Shelf life is 2 years when stored unopened, dry and cool conditions.

### **Packing**

0,75 / 2,50 / 15,00 lt

### Hazard Classification

- Flame. Liquid 2, H225: Highly flammable liquid and vapor.
- Asp. Toxicity 1, H304: Fatal if enters airways and swallowed.

### **Precautionary Statements**

### -Precautions

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



TECHNICAL DATA SHEET

Document No: TDS.SL.037 Revision Date / No: 01.10.2018 / 00

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical / ventilating / light equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P280: Wear protective gloves / protective clothing / eye protection / face protection.

#### -Intervention

P301+310: IF SWALLOWED: Immediately call the National POISON CENTER at Phone No: 114 or a doctor / physician.

P303+361+353: ON CONTACT WITH SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.

P331: DO NOT induce vomiting.

P370+P378: In case of fire: Use alcohol, foam, dry chemicals and carbon dioxide to extinguish.

#### -Storage

P403+235: Store in a well ventilated place. Keep cool.

P405: Store locked up.

#### -Disposal

P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste." Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

## Warning Word

Danger

### **Hazard Signs**



