



## Semi-Gloss Yacht Varnish

Urethane alkyd resin combination based, semi-gloss topcoat forming exterior varnish.

### Areas of Use

A varnish which is used for wooden surfaces as well as all kinds of interior and exterior surfaces of marine vessels and has excellent protective features, and is resistant to U.V. ray.

### Specification

- Gives semi - gloss appearance to the surfaces.

- Protective
- High resistant to U.V. lights
- Decorative
- Yellowing resistant
- Perfect working properties
- Fast drying

### Application

All surfaces must be free of oil, grease, paint and dirt. Apply 2 – 3 coats of **Bianca Semi-Gloss Yacht Varnish**. Wait for 24 hours between coats. Sanding is recommended after each coat.

### Thinning (Volume)

10 % to be thinned with synthetic thinner. Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.

### Drying Period (20°C)

Set to touch: 1/2 – 2 hours  
Dust Free: 2 – 4 hours  
Dry Hard: 4 – 6 hours

### Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 14 – 18 m<sup>2</sup>.

### Flash Point

38°C

### Storage

Shelf life is 2 years when stored unopened, dry and cool conditions.

### Packing

0,75 / 2,50 / 12,00 lt

### Hazard Classification

- Flame. Liquid 3, H226: Flammable liquid and vapor.
- Asp. Toxicity 1, H304: Fatal if enters airways and swallowed.
- Skin Irritation 2 H315: Causes skin irritation
- BHOT Repeated Exposure1, H372: Causes damage to organs through prolonged or repeated exposure.
- BHOT Repeated Exposure3, H336: May cause drowsiness or dizziness.
- Aquatic Chronic 2, H411: Toxic to aquatic life with long-lasting effects.

### **Precautionary Statements**

#### **-Precautions**

- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233: Keep container tightly closed.  
P240: Ground / bond container and receiving equipment.  
P241: Use explosion-proof electrical / ventilating / light equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P260: Do not breathe dust / fumes / gas / mist / vapors / spray.  
P261: Avoid breathing dust / fumes / gas / mist / vapors / spray.  
P264: Wash thoroughly with soap and water after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only outdoors or in a well-ventilated area.  
P273: Avoid release to the environment.  
P280: Wear protective gloves / protective clothing / eye protection / face protection.

#### **-Intervention**

- P301+310: IF SWALLOWED: Immediately call the National POISON CENTER at Phone No: 114 or a doctor / physician.  
P302+352: IF ON SKIN: Wash with plenty of water and soap.  
P303+361+353: ON CONTACT WITH SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.  
P304+340: IF INHALED: Remove person, if having difficulties in breathing, to fresh air and keep comfortable for breathing.  
P312: Call a POISON CENTER / doctor / physician if you feel unwell.  
P314: Get Medical advice / attention if you feel unwell.  
P321: Specific treatment required (see the label).  
P331: DO NOT induce vomiting.  
P332+P313: If skin irritation occurs: Get medical assistance / attention.  
P362: Take off and wash prior to use any contaminated clothing.  
P370+P378: In case of fire: Use alcohol, foam, dry chemicals and carbon dioxide to extinguish.  
P391: Collect spillage.

#### **-Storage**

- P403+235: Store in a well ventilated place. Keep cool.  
P405: Store locked up.

#### **-Disposal**

- P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste."  
Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

### **Warning Word**

Danger

### **Hazard Signs**

