



Cement Cleaner

Cement cleaner containing surface active materials

It enables cement based materials to be effectively cleaned from floor and wall coverings such as ceramics and granite ceramics.

Application Area

It is used for cleaning of contaminated floors with mortar, grout filler, cement based construction residues.

Application Surface

- Ceramic, granite ceramic, natural stones,
- Consult us for all the other application surfaces.

Application Border

It can not be applied on glazed or polished surfaces.

Warnings and Recommendations

When **Bianca Cement Cleaner** is applied, it should be worn gloves and avoided from the contact with eyes and skin.

Surface Preparation

The surface must be durable.

Application Condition

- Ambient temperature is between the +5°C and +30°C.
- It should be avoided from the application in very humid and / or very hot weather.

Application

- **Bianca Cement Cleaner** can be used in manual application up to the areas which can be reached in one time, with the help of a sponge or roller; In application by machine, it is applied in an area of 3 - 4 m² . It is waited 1 - 2 minutes and then the cleaning process is started.
- Application can be repeated in very dirty areas. **Bianca Cement Cleaner** is cleaned from the surface by washing with plenty of water.

Consumption

50 - 70 ml/m²

Packing

1,00 / 5,00 lt

Color

Transparent

Application Tools

Sponge, lambskin roller, silim machine.

Shelf Life

It is 5 years from the date of production provided that the mouth of the packaging is not opened in dry and cool environment. When not in use, the mouth of the packaging should be tightly closed. Packages must be protected from frozen.