



Triplo - Monotype Anticorrosive Paint

It is a synthetic alkyd resin based, anti-corrosion, iron-steel-sheet primer and top coat paint that prevents rust formation.

Areas of Use

In iron constructions, doors, windows, fences, wood etc. It is used as bright topcoat paint on interior and exterior surfaces of building elements.

Specification

- Has high and lasting brightness.
- It has maximum resistance against yellowing.
- It has excellent sealing and spreading properties.

- No brushing and no flow.
- It is easily handled with brush.
- It has maximum resistance against dust holding and pollution over time.
- It is resistant to chemical cleaning materials used in houses.
- Protect metal surfaces against rust.
- Creates very good adherence on application surface.
- It saves labor and time.

Application

Surfaces to be applied include oil, rust, dust, etc. it must be free from pollution. Rusty surfaces should be sandblasted, brushed and wiped with a wire brush. It must be paid attention that surface and ambient temperature is between +5°C and +30°C during application. **Bianca Triplo Monotype Paint** will be applied for the first time, old and new metal surfaces will be sanded to the shiny surface, then the oil and dirt on the surface should be removed from the surface with synthetic thinner and immediately painted one or two times with **Bianca Triplo Monotype Paint**.

Thinning (Volume)

10 – 15 % to be thinned with synthetic thinner. Stir thoroughly before using the paint and do not mix it with a paint of other brands.

Drying Period (20°C)

Touch Drying: 2 hours
Anti-Dust Retention: 4 - 6 hours
Set Drying: 24 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the 15 – 20 m².

Flash Point

38°C

Storage

It is 2 years in an unopened original container at ambient temperature.

Packing

0,75 / 2,50 / 15,00 lt

Hazard Classification

- Flame. Liquid 3, H226: Flammable liquid and vapor.
- Asp. Toxicity 1, H304: Fatal if enters airways and swallowed.
- Breastfeeding H362: May cause harm to breast-fed children.

- Aquatic Chronic 3, H412: Harmful to aquatic life with long-lasting effects.
- BHOT Repeated Exposure3, H336: May cause drowsiness or dizziness.

Additional Hazard Information Statements

- EUH066: Could cause dryness and cracking of skin upon repeated exposure

Precautionary Statements

- Precautions

- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233: Keep container tightly closed.
- P241: Use explosion-proof electrical / ventilating / light equipment.
- P242: Use only non-sparking tools.
- P243: Take precautionary measures against static discharge.
- P261: Avoid breathing dust / fumes / gas / mist / vapors / spray.
- P271: Use only outdoors or in a well-ventilated area.
- P273: Avoid release to the environment.
- P280: Wear protective gloves / protective clothing / eye protection / face protection.

- Intervention

- P301+310: IF SWALLOWED: Immediately call the National POISON CENTER at Phone No: 114 or a doctor / physician.
- P304+340: IF INHALED: Remove person that is exposed to fresh air and keep comfortable for breathing.
- P303+361+353: ON CONTACT WITH SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
- P312: Call a POISON CENTER / doctor / physician if you feel unwell.
- P331: DO NOT induce vomiting.
- P370+P378: In case of fire: Use alcohol, foam, dry chemicals and carbon dioxide to extinguish.

- Storage

- P403+233: Store in a well ventilated place. Keep container tightly closed.
- P403+235: Store in a well ventilated place. Keep cool.
- P405: Store locked up.

- Disposal

- P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste."
Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

Warning Word

Danger

Hazard Signs

