



Astaria - Extra primer that adheres to all surfaces

Acrylic resin based, excellent adhesion, fast drying, silky matt gloss primer.

Areas of Use

It is used on interior and exterior facades of iron, steel, aluminum, zinc (galvanized surfaces), hard pvc, copper and wood surfaces.

Specification

- Protects metal surfaces against rust.
- Perfect adhesion to the surface.
- Dries fast.
- After drying, water-based, solvent-based, epoxy and cellulosic paints can be applied easily.
- It is resistant to thinners used for cellulosic varnishes (nitro cellulose based).
- It can be applied all kinds of climate.
- Does not contain lead.

Application

Surfaces should be cleaned with Bianca Cellulosic Thinner. All kinds of dust, dirt, oil are removed from the surfaces. Primer diluted with 5-15% Bianca Cellulosic Thinner is applied with paint gun. The primer must be thoroughly mixed before use.

Wood surface; It is recommended to apply Bianca Wood Protector on raw wood surfaces before Bianca Astaria. In practice, the average moisture content of hardwoods should not exceed 10% and for softwoods it should not exceed 13%. Interior and exterior façades can be applied in one coat.

Iron and steel surfaces; During application and until the products are completely dry, the ambient and surface temperature should be between + 5°C and + 30°C. Surfaces should be protected from frost. It can be applied by brush, roller and spraying.

Zinc (galvanized surfaces); It is recommended to apply Bianca Astaria to the zinc surfaces on the facades.

Thinning (Volume)

To be thinned with 10 - 15 % of **Bianca Cellulosic Thinner**.

Drying Period (20°C)

Set to touch: 20 - 30 min.

Dust repelling: 1 - 2 hours

Hardening: 3 - 4 hours

Coverage

Depending on the application and the surface, for single layer, 1 liter will be enough to cover the 10 – 11 m².

Storage

Shelf life is 2 years when stored unopened, dry and cool conditions.

Packing

0,75 / 2,50 / 15,00 lt

Hazard Classification

- Flame. Liquid 2, H225: Highly flammable liquid and vapour
- Asp. Toxicity 1, H304: Fatal if enters airways and swallowed.
- BHOT Repeated Exposure 2, H373: May cause damage to organs through prolonged or repeated exposure.

- BHOT Repeated Exposure 3, H336: May cause drowsiness and dizziness.
- Skin Irritation 2: Causes skin irritation
- Aquatic Chronic 2. H361d: Suspected of damaging the unborn child

Precautionary Statements

-Precautions

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical / ventilating / light equipment.

P243: Take precautionary measures against static discharge.

P260: Do not breathe dust / fumes / gas / mist / vapours / spray.

P280: Wear protective gloves / protective clothing / eye protection / face protection.

-Intervention

P301+310: IF SWALLOWED: Immediately call the National POISON CENTER at Phone No: 114 or a doctor / physician.

P314: Get medical advice/attention if you feel unwell.

P331: DO NOT induce vomiting.

P370+P378: In case of fire: Use alcohol, foam, dry chemicals and carbon dioxide to extinguish.

P302+P352: IF ON SKIN: Wash with plenty of water/...

P303+353+361: ON CONTACT WITH SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+340: IF INHALED: Remove person that is exposed to fresh air and keep comfortable for breathing.

P370+P378: In case of fire: Use alcohol, foam, dry chemicals and carbon dioxide to extinguish.

P308+313: IF exposed or under effect: obtain medical attention / treatment

-Storage

P403+235: Store in a well ventilated place. Keep cool.

-Disposal

P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste."

Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

Warning Word

Danger

Hazard Signs

