

TECHNICAL DATA SHEET
Document No: TDS.SL.050

Revision Date / No:30.11.2018 / 00



Esterno UV - Exterior Wood Varnish

Pre-protected (impregnated) solvent based, silky matt special wood varnish for exterior wood.

Areas of Use

It is used on wooden surfaces in interior and exterior environments, door and window frames, pergolas, wooden garden furniture, marine vehicles, furniture elements that require protection of natural appearance and wood works.

Specification

- Protects against pest and fungus that damage wood.
- Constructive wood preservation methods reduce the risk of decay.
- Due to its higher solids content, it prevents gnawing from wasps.
- Abrasive U.V. resistant to sunlight.
- Dries in a short time. Nem ayarlayıcı özelliktedir.
- · Populates in depth.
- · No crusting, no shedding.
- · Can be applied without sanding.
- · Easy to apply.
- · Provides decorative appearance to wood.
- 3-in-1: Can be used as pre-preservation, primer and topcoat.

Application

Old painted surfaces should be completely cleaned. Impurities such as resin, sanding dust on the wooden surfaces to be painted should be removed. Application should be done with brush or roller in 2 or 3 coats. Wait 24 hours between layers. Surface and ambient temperature should be between + 5°C and + 30° C during application..

Thinning (Volume)

Ready to use.

Drying Period (20°C)

Hardening drying: 12 hours

Second layer application: 24 hours

Coverage

Depending on the application and the surface, for single layer, 1 litre will be enough to cover the $12 - 15 \text{ m}^2$.

Flash Point

36°C

Storage

Shelf life is 1 years when stored unopened, dry and cool conditions.

Packing

0,75 / 2,50 / 15,00 It

Hazard Classification

- Flame. Liquid 3; H226: Flammable liquid and vapor.
- Acute Tox. 4; H332: Harmful if inhaled
- Asp. Toxicity 1; H304: Fatal if enters airways and swallowed.
- BHOT Repeated Exposure1; H372: Causes damage to organs through prolonged or repeated exposure.



TECHNICAL DATA SHEET
Document No: TDS.SL.050
Revision Date / No:30.11.2018 / 00

- Carcinogen 1B; H350: May cause cancer (carcinogenic).
- Muta. 1B: H340 May cause genetic defects.

Precautionary Statements

- Precautions

P201: Read special instructions before use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves / protective clothing / eye protection / face protection.

- Intervention

P303+361+353: ON CONTACT WITH SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+340: IF INHALED: Remove person, if having difficulties in breathing, to fresh air and keep comfortable for breathing.

P308+313: IF exposed or under effect: obtain medical attention / treatment.

P370+P378: In case of fire: Use alcohol, foam, dry chemicals and carbon dioxide to extinguish.

- Disposal

P501: Dispose of contents / container according to the "Regulation on the Disposal of Hazardous Waste." Disposal together with household waste is prohibited. Prevent the material reaching the sewage.

Warning Word

Danger

Hazard Signs





