



Interior Façade Paste

Is an inner facade surface restoration paste, which has a flexible structure and an acrylic copolymer emulsion base.

Areas of Use

Interior Putty is a material which can be applied on Concrete, Exposed Concrete, Aerated Concrete, Stone fiber, asbestic tile, mdf and osb, previously applied paint, plaster and other similar mineral based surfaces to fill the area and to correct the defects of surface,

Application

The surfaces should be in a solid, clean, and dry state and should be self-supporting. In order to enable the paste to stick better to the surfaces such as aerated concrete, after application of transparent property primers (**Bianca Insulation Primer, Vals Primer**) is performed, puttying process should be started. Otherwise the putty may collapse from the surface since it won't be able to provide adherence to the surface due to the sudden water losses. Puttying by using putty knife or flexible trowel shall be made on Concrete, Exposed Concrete, Aerated Concrete, Stone fibre, asbestic tile, mdf and osb, previously applied paint, plaster and other similar mineral based, less absorptive, not chalking inner façades with pure plaster after applying one layer of our pigment primers (Inner Facade Primer). Take care to ensure the ambient temperature is +5°C during application.

Thinning (Volume)

Ready for using, don't thin.

Drying Period (20°C)

Second Layer Application: 24 hours.

Coverage

Depending on the application and the surface, for single layer, 1 kg will be enough to cover the 0,6 - 1,5 m².

Storage

Shelf life 1 year when stored unopened, in the original container.

Packing

4,00 / 25,00 kg

Health, Safety and Environment

- While applying paint wear eye protective glasses
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ensure maximum ventilation during application and drying.
- Keep container tightly closed and keep out of reach of children.
- Protect from frost and extreme temperature.
- Do not pour the remaining paint into the sink and toilet.
- Clean paint brush and roller with water after each application.
- Ensure this pack is stored upright and secure during transportation.